

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 July 2005 (14.07.2005)




PCT

(10) International Publication Number  
**WO 2005/064733 A1**

- (51) International Patent Classification<sup>7</sup>: **H01M 10/40**, 10/39, 10/36, 6/14, 6/16, H01G 9/02
- (21) International Application Number: PCT/EP2004/053182
- (22) International Filing Date: 30 November 2004 (30.11.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 03104985.1 29 December 2003 (29.12.2003) EP
- (71) Applicant (for all designated States except CA, US): **SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V.** [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).
- (72) Inventors; and  
(75) Inventors/Applicants (for US only): **BEST, Adam Samuel** [AU/NL]; Julianalaan 136, NL-2628 NL Delft (NL). **LANDHEER, Hiske** [NL/NL]; Julianalaan 136, NL-2628 NL Delft (NL). **OOMS, Franciscus Güntherus Bernardus** [NL/NL]; Julianalaan 136, NL-2628 NL Delft (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,

[Continued on next page]

(54) Title: ELECTROCHEMICAL ELEMENT FOR USE AT HIGH TEMPERATURES



(57) Abstract: An electrochemical element for use at a high temperature has an anode, a cathode comprising an intercalation material having an upper reversiblepotential-limit of at most 4 V versus Li/Li<sup>+</sup> as active material, and an electrolyte arranged between the cathode and anode, which electrolyte comprises an ionic liquid with an anion and a cation comprising a pyrrolidinium ring structure having four Carbon atoms and one Nitrogen atom. Experiments revealed that rechargeable batteries comprising such an intercalation material and N-R<sub>1</sub>-N-R<sub>2</sub>-pyrrolidinium, wherein R<sub>1</sub> and R<sub>2</sub> are alkyl groups and R<sub>1</sub> may be methyl and R<sub>2</sub> may be butyl or hexyl, are particularly suitable for use at a temperature of up to about 150 degrees Celsius and may be used in oil and/or gas production wells.



TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**(84) Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*